



US006492965B2

(12) **United States Patent**
Kasahara et al.

(10) **Patent No.:** **US 6,492,965 B2**
 (45) **Date of Patent:** ***Dec. 10, 2002**

(54) **DISPLAY DEVICE AND LUMINANCE CONTROL METHOD THEREFOR**

(75) **Inventors:** **Mitsuhiro Kasahara, Hirakata (JP); Yuichi Ishikawa, Ibaraki (JP); Tomoko Morita, Hirakata (JP)**

(73) **Assignee:** **Matsushita Electric Industrial Co., Ltd., Osaka (JP)**

(*) **Notice:** Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) **Appl. No.:** **09/994,775**

(22) **Filed:** **Nov. 28, 2001**

(65) **Prior Publication Data**

US 2002/0033814 A1 Mar. 21, 2002

Related U.S. Application Data

(62) Division of application No. 09/856,161, filed as application No. PCT/JP00/06212 on Sep. 11, 2000.

(30) **Foreign Application Priority Data**

Oct. 4, 1999 (JP) 11-283228

(51) **Int. Cl.⁷** **G09G 3/28**

(52) **U.S. Cl.** **345/63; 345/211; 345/690**

(58) **Field of Search** **345/63, 101, 204, 345/589, 596, 599, 690, 691**

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,191,505 B1 2/2001 Matsuyama
 6,270,061 B1 8/2001 Bouquet et al.

FOREIGN PATENT DOCUMENTS

JP 6282241 10/1994

JP	9-6283	1/1997
JP	9198005	7/1997
JP	9288467	11/1997
JP	9'288467	11/1997
JP	10215424	8/1998
JP	11194745	7/1999
JP	11 194745	7/1999
JP	11212517	8/1999
JP	11 231828	8/1999
JP	11231828	8/1999
JP	11288244	10/1999
JP	11 288244	10/1999
JP	11-283228	10/2001
JP	2001200087	10/2001

OTHER PUBLICATIONS

An English Language abstract of JP 6-282241.

An English Language abstract of JP 9-6283.

An English Language abstract of JP 9-198005.

An English Language abstract of JP 10-215424.

An English Language abstract of JP 11-194745.

An English Language abstract of JP 11-288244.

An English Language abstract of JP 11-231828.

An English Language abstract of JP 9-288467.

An English Language abstract of JP 11-212517.

ITE '98: 1998 ITE Annual Convention, along with a partial English Translation.

Primary Examiner—Kent Chang

(74) *Attorney, Agent, or Firm*—Greenblum & Bernstein, P.L.C.

(57) **ABSTRACT**

A temperature difference estimated value is found from a video signal using a temperature estimated value representing the temperature of the panel outer periphery of a display screen of a PDP and a reference value representing the temperature of the panel outer periphery of the PDP which is outputted from a panel periphery temperature setter by a temperature difference estimator, and the luminance of an image displayed on a display is controlled depending on the temperature difference estimated value by a controller and a brightness controller.

9 Claims, 18 Drawing Sheets

